

Product Data Sheet

Liquid Release Agent



Liquid Release Agent is a colorless, bubblegum scented petroleum distillate. This release agent has been formulated to release any decorative imprinting tool from concrete or polymer modified cementitious topping.

Liquid Release Agent provide a lubricating barrier that protect and prolongs the life of stamping tools and evaporates from the cementitious surface leaving minimal residue.

APPLICATIONS

Liquid Release Agent is most commonly used for:

- Stamped Concrete
- Stamped Overlay
- Texture systems
- Imprinting
- Stamp tools

BENEFITS

Liquid Release Agent has a large list of benefits, including but not limited to;

- Colorless
- Bubblegum scented
- Prolongs life of tools

APPLICATION

Liquid Release Agent is used by misting the cementitious surface with a pump-up sprayer. Imprinting tools must have their texture face saturated prior to stamping. Apply as much release as can be covered with each tools and within a few minutes in temperatures above 40oF upwards.

Direct sunlight and windy conditions will accelerate the evaporative properties.

CLEAN-UP

Before the product dries; spill and tools can be cleaned up with a solvent such as xylene or acetone.

DISPOSAL

Follow local guidelines for disposing hazardous products.

PACKAGING

5 Gal (pail)

COVERAGE

Approx. 204 ft² per Gallon

VOC Content

0g/L

APPLICATION TEMPERATURE

40°F above

ODOR

Bubblegum

CURE TIME

Not applicable

APPEARANCE

Colorless'

SHELF LIFE

Under normal: when kept dry and moisture free out of direct sunlight, the shelf life of an un-opened container is 12 months from the date of purchase. Storage must be under roof and off the floor. Avoid extreme temperatures Rotate inventory to maintain product that is within limits

Product Data Sheet

Liquid Release Agent



DISPOSAL

Follow local guidelines for disposing hazardous products.

LIMITATIONS

- For use by trained professionals. .

CAUTIONS

KEEP OUT OF REACH OF CHILDREN. Product is flammable. Avoid sources of ignition. Keep areas of installation well ventilated.

Inhalation: Use NIOSH approved respirator for organic vapors.

Skin Contact: Skin contact may cause irritation. Remove contaminated clothing immediately and wash effected area with soap and water. Wash clothing before using again. If symptoms persist seek medical attention immediately.

Eyes: Wear Safety eye protection when installing this product. If contact occurs, flush eye with water for 15 minutes, seek medical attention.

Further Information

Information relating to the safe handling of this product can be found in the Material Safety Data Sheet. Local Regulations concerning the safe handling of solvent based materials must be observed. Suitable protective clothing including eye protection must be worn at all times.